

BOY Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

| RING DIA. | NOSE ANGLE | SCREW THREAD | 3T Style |
|-----------|------------|----------------|--------------|
| 14MM | 84 | M8X1.25-LH | \$316 |
| 16MM | 76 | M8X1.25-LH | \$316 |
| 18MM | 90 | M10X1.5-LH | \$316 |
| 22MM | 90 | M12X1,75-LH | \$316 |
| 24MM | 90 | M12X1.75-LH | \$316 |
| 28MM | 90 | M12X1.75-LH | \$316 |
| 28MM | 90 | M12X1.75-LH | \$316 |
| 29MM | 90 | M12X1,75-LH | \$316 |
| 32MM | 60 | M14X2.0-LH | \$316 |
| 32MM | 90 | M14X2.0-LH | \$316 |
| 36MM | 90 | M16X2.0-LH | \$316 |
| 38MM | 90 | M16X2.0-LH | \$316 |
| 42MM | 90 | M16X2.0-LH | \$333 |
| 42MM | 90 | M16X2.0-LH | \$333 |
| 48MM | 90 | ,18X2.5 TPI-LH | \$352 |