

CINCINNATI Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
16MM	60	M8X1.0-LH	\$316
18MM	60	M9X1.25-LH	\$316
18MM	60	M8X1.25-LH	\$316
18MM	90	M10X1.5-LH	\$316
20MM	20	M10X1.5-LH	\$316
20MM	90	M10X1.5-LH	\$316
22MM	20	M12X1.75-LH	\$316
22MM	60	M10X1.5-LH	\$316
22MM	90	M12X1.75-LH	\$316
22MM	60	M12X1.75-LH	\$316
24MM	60	M10X1.5-LH	\$316
26MM	90	M16X2.0-LH	\$316
26MM	60	M14X2.0-LH	\$316
28MM	60	M12X1.75-LH	\$316
28MM	90	M16X2.0-LH	\$316
28MM	90	M16X2.0-LH	\$316
28MM	8.5	M16X2.-LH	\$316
x 32MM	90	M18X2.5-LH	\$316
x 32MM	60	M18X2.5-LH	\$316
x 32MM	60	M18X2.5-LH	\$316
35MM	13	.750-10 TPI-LH	\$316
35MM	60	M18X2.5-LH	\$316
36MM	60	M18X2.5-LH	\$316
36MM	60	M20X2.5-LH	\$316
36MM	90	M20X2.5-LH	\$316
36MM	90	.750-10 TPI-LH	\$316
40MM	60	M20X2.5 LH	\$316
40MM	60	M20X2.5-LH	\$316
40MM	90	M20X2.5-LH	\$316
42MM	60	M22X2.5-LH	\$316

x = Requires thread adapter.

CINCINNATI Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
44MM	90	M24X3.0-LH	\$316
45MM	60	M22X2.5-LH	\$330
48MM	90	M24X3.0-LH	\$352
48MM	90	M24X3.0-LH	\$352
48MM	60	M24X3.0-LH	\$352
50MM	60	M24X3.0-LH	\$352
55MM	60	M27X3.0-LH	\$425
56MM	20	M30X3.5-LH	\$439
56MM	60	M30X3.5-LH	\$439
60MM	60	M27X3.0-LH	\$495
64MM	25	M36X4.0-LH	\$505
64MM	90	M36X4.0-LH	\$505
64MM	60	M36X4.0-LH	\$505
65MM	60	M30X3.5-LH	\$516
70MM	60	M36X4.0-LH	\$586
70MM	22	M36X4.0-LH	\$586
80MM	60	M42X4.5-LH	\$741
90MM	60	M48X5.0-LH	\$793
90MM	20	M48X5.0-LH	\$793
100MM	60	M52X5.0-LH	\$978
110MM	60	M56X5.5-LH	\$1096
110MM	60	M56X5.5-LH	\$1096
125MM	60	M64X6.0-LH	\$1245
140MM	60	M72X6.0-LH	\$1400
160MM	60	M80X6.0-LH	\$1752
180MM	60	M90X6.0-LH	\$2021
200MM	60	M100X6.0-LH	Quote
1"	90	.438-20 TPI-LH	\$316
1.188"	90	.500-13 TPI-LH	\$316
1.313"	90	.625-11 TPI-LH	\$316

x = Requires thread adapter.

CINCINNATI Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
1.313"	120	.625-11 TPI-LH	\$316
1.625"	120	.750-10 TPI-LH	\$316
1.625"	90	.750-10 TPI-LH	\$316
1.875"	90	.750-10 TPI-LH	\$352
2"	120	1.000-8 TPI-LH	\$352
2"	90	1.000-8 TPI-LH	\$352
2.25"	90	1.000-8 TPI-LH	\$426
2.5"	120	1.250-12 TPI-LH	\$508
2.5"	90	1.250-7 TPI-LH	\$508
2.75"	120	1.250-12 TPI-LH	\$548
2.75"	90	1.250-7 TPI-LH	\$548
3.25"	120	1.500-12 TPI-LH	\$595
3.25"	90	1.500-6 TPI-LH	\$595
3.5"	90	1.500-6 TPI-LH	\$637
3.5"	120	1.500-12 TPI-LH	\$637
3.5"	20	1.500-6 TPI-LH	\$637
3.75"	60	1.875-8 TPI-LH	\$826
3.75"	120	1.875-8 TPI-LH	\$826
4"	90	1.750-6 TPI-LH	\$885
4.5"	90	2.000-6 TPI-LH	\$987
4.5"	120	2.000-12 TPI-LH	\$987
4.5"	20	2.000-6 TPI-LH	\$987
5.25"	120	2.250-12 TPI-LH	\$1309
5.25"	90	2.250-6 TPI-LH	\$1309
6"	120	2.500-12 TPI-LH	\$1586
6"	90	2.500-6 TPI-LH	\$1586
8"	120	3.500-12 TPI-LH	Quote
8"	90	3.500-6 TPI-LH	Quote
8"	120	3.500-12 TPI-LH	Quote

x = Requires thread adapter.