

FARREL Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
1.25"	45	.500-13 TPI-LH	\$316
1.625"	45	.750-10 TPI-LH	\$316
2"	45	1.000-8 TPI-LH	\$351
2.1"	46	1.000-8 TPI-LH	\$351
2.5"	45	1.250-7 TPI-LH	\$522
2.8"	45	1.375-8 TPI-LH	\$580
3"		M39X4.0-LH	Quote
3.25"	45	1.500-8 TPI-LH	\$657
3.6"	50	1.625-8 TPI-LH	\$722
4.25"	45	2.000-8 TPI-LH	\$998
4.25"	60	2.000-8 TPI-LH	\$998
4.75"	45	2.250-8 TPI-LH	\$1133
5"		2.250-6 TPI-LH	Quote
5.25"	90	2.750-6 TPI-LH	Quote
5.25"	105	2.75-6 TPI-LH	Quote
6"		3.000-6 TPI-LH	Quote
6.375"	60	3.250-6 TPI-LH	Quote