

HPM Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
1.1875"	60	.500-20 LH	\$316
1.375"	60	.5625-18 LH	\$316
1.375"	60	.625-11 TPI-LH	\$316
1.5"	60	.625-11 TPI-LH	\$316
1.625"	60	.750-16 TPI-LH	\$316
1.750"	60	.750-10 TPI-LH	\$337
2"	60	.875-9 TPI-LH	\$351
2.125"	60	1.000-8 TPI-LH	\$351
2.25"	60	1.000-8 TPI-LH	\$429
2.3125"	60	1.000-8 TPI-LH	\$429
2.5"	60	1.125-7 TPI-LH	\$505
2.625"	60	1.250-8 TPI-LH	\$516
2.75"			\$516
3"	60	1.625-6 TPI-LH	\$548
3"	30	1.625-06 TPI-LH	\$548
3.25"	60	1.625-6 TPI-LH	\$640
3.25"	40	1.750-6 TPI-LH	\$640
3.5"	30	1.750-6 TPI-LH	\$688
3.5"	60	1.750-6 TPI-LH	\$688
4"	60	2.000-6 TPI-LH	\$773
4"	60	2.250-8 TPI-LH	\$773

HPM Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
4.5"	60	2.250-6 TPI-LH	\$989
4.75"		2.500-6 TPI-LH	Quote
5"	90	2.250-6 TPI-LH	Quote
5"	45	2.250-6 TPI-LH	Quote
5"	60	2.250-6 TPI-LH	Quote
5.25"	60	2.750-6 TPI-LH	Quote
6"	60	3.000-6 TPI-LH	Quote
6"	20	3.000-6 TPI-LH	Quote
7"		3.500-6 TPI-LH	Quote
8"	60	4.000-6 TPI-LH	Quote
22MM	60	M10X1.5-LH	\$316
30MM		M14X2.0-LH	\$316
35MM		M18X2.5-LH	\$316
36MM		M16X1.5-LH	\$316
40MM		M20X2.5-LH	\$328
42MM	60	M20X2.5-LH	\$328
45MM		M20X2.5-LH	\$337
50MM	60	M24X3.0-LH	\$352
50MM	60	M20X2.0-LH	\$352
55MM	50	M27X3.0-LH	\$426

HPM Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
60MM	60	M30X2.0-LH	\$531
65MM		M30X3.5-LH	\$550
70MM	60	M36X2.0-LH	\$584
70MM	22	M36X4.0-LH	\$584
80MM	30	M42X4.5-LH	\$772
85MM	60	M48X5.0-LH	\$772
85MM	60	M45X4.5-LH	\$772
85MM	22	M45X4.5-LH	\$772
90MM		M48X5.0-LH	\$780
100MM	60	M60X5.5-LH	\$978
100MM	60	M52X5.0-LH	\$978
110MM		M64X4.0-LH	\$1096
120MM	60	M64X6.0-LH	\$1225
125MM	60	M64X6.0-LH	\$1430
140MM		2.750-6 TPI-LH	Quote
160MM	30	3.250-6 TPI-LH	Quote
180MM		M90X6.0-LH	Quote
200MM		4.000-4 TPI-LH	Quote
225MM		4.750-4 TPI-LH	Quote
230MM	90	4.000-8 TPI-LH	Quote