

IMPCO Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
1.125"	60	.500-13 TPI-LH	\$316
1.1875"	40	1.000-8 TPI-LH	\$316
1.25"	60	.500-13 TPI-LH	\$316
1.5"	40	.875-9 TPI-LH	\$316
1.625"	40	.875-9 TPI-LH	\$316
1.813"	40	1.000-8 TPI-LH	\$337
2"	40	1.125-8 TPI-LH	\$372
2"	60	.8125-12 TI-12	\$372
2"	40	.875-9 TPI-LH	\$372
2.125"	40	1.250-7 TPI-LH	\$439
2.25"	40	1.250-8 TPI-LH	\$526
2.375"	40	1.375-8 TPI-LH	\$552
2.375"	40	1.375-6 TPI-LH	\$552
2.5"	40	1.500-6 TPI-LH	\$560
x 2.5"	40	1.500-6 TPI-LH	\$560
2.5"	40	1.250-7 TPI-LH	\$560
2.5"	40	1.375-6 TPI-LH	\$560

x = Requires thread adapter.

IMPCO Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
2.8125"	40	1.500-8 TPI-LH	\$611
x 3"	40	1.750-5 TPI-LH	\$661
3.25"x	40	2.000-8 TPI-LH	\$740
3.5"	40	2.000-4.5 TPI-LH	\$792
x 3.5"	40	1.753-6 TPI-LH	\$792
x 3.688"	40	2.000-8 TPI-LH	\$850
x 3.75"	40	2.125-8 TPI-LH	\$898
4.25"	40	2.250-4.5 TPI-LH	\$1157
4.75"	36	2.250-4.5 TPI-LH	\$1225
4.75"	44	2.250-8 TPI-LH	\$1225
x 4.75"	40	2.750-4 TPI-LH	\$1293
5.5"	40	2.750-8 TPI-LH	Quote
5.5"	45	2.500-6 TPI-LH	Quote
6"	90	3.000-6 TPI-LH	Quote

x = Requires thread adapter.