

# JSW Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

| RING DIA. | NOSE ANGLE | SCREW THREAD   | 3T Style     |
|-----------|------------|----------------|--------------|
| 22MM      | 90         | M10X1.5-LH     | <b>\$316</b> |
| 25MM      | 30         | M12X1.75-LH    | <b>\$316</b> |
| 25MM      | 90         | M12X1.75-LH    | <b>\$316</b> |
| 28MM      | 30         | M16X2.0-LH     | <b>\$316</b> |
| 30MM      | 60         | M12X1.75-LH    | <b>\$316</b> |
| 32MM      | 30         | M18X2.5-LH     | <b>\$316</b> |
| 35MM      | 18         | TR20X3.0-LH    | <b>\$316</b> |
| 40MM      | 18.5       | TR22X3.0-LH    | <b>\$337</b> |
| 40MM      | 21         | TR22X3.0-LH    | <b>\$337</b> |
| 40MM      | 22         | M20X2.5-LH     | <b>\$337</b> |
| 45MM      | 20         | TR27X3.0-LH    | <b>\$364</b> |
| 45MM      | 22         | TR24X3.0-LH    | <b>\$364</b> |
| 45MM      | 22         | TR27X3.0-LH    | <b>\$364</b> |
| x 45MM    | 22         | .750-10 TPI-LH | <b>\$364</b> |
| 45MM      | 60         | M22X2.5-LH     | <b>\$364</b> |
| 45MM      | 90         | TR24x3.0-LH    | <b>\$364</b> |
| 46MM      | 17         | TR24X3.0-LH    | <b>\$364</b> |
| 51MM      | 20         | TR27X3.0-LH    | <b>\$400</b> |
| 51MM      | 22         | TR27X3.0-LH    | <b>\$400</b> |
| 52MM      | 22         | TR32X3.0-LH    | <b>\$426</b> |
| 53MM      | 18         | TR28X3.0-LH    | <b>\$426</b> |
| 53MM      | 90         | M30X3.5-LH     | <b>\$426</b> |

x = Requires thread adapter.

# JSW Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

| RING DIA. | NOSE ANGLE | SCREW THREAD    | 3T Style      |
|-----------|------------|-----------------|---------------|
| x 58MM    | 18         | TR36X3.0-LH     | <b>\$453</b>  |
| 58MM      | 20         | TR36X3.0-LH     | <b>\$453</b>  |
| x 60MM    | 23         | TR35X3.0-LH     | <b>\$509</b>  |
| 63MM      |            |                 | <b>\$527</b>  |
| x 66MM    | 14/60      | TR38X3.0-LH     | <b>\$527</b>  |
| x 68MM    | 22         | TR40X3.0-LH     | <b>\$559</b>  |
| 72MM      | 16         | TR40X3.0-LH     | <b>\$625</b>  |
| 72MM      | 16         | TR40X3.0-LH     | <b>\$625</b>  |
| x 76MM    | 16/30      | TR40X3.0-LH     | <b>\$691</b>  |
| 83MM      | 19         | TR42X3.0-LH     | <b>\$789</b>  |
| x 84MM    | 18/30      | TR47X3.0-LH     | <b>\$862</b>  |
| 84MM      | 19         | TR47X3.0-LH     | <b>\$862</b>  |
| 84MM      | 19         | TR47X3.0-LH     | <b>\$862</b>  |
| 86MM      | 20         | 1.500-08 TPI-LH | <b>\$884</b>  |
| 86MM      | 20/36      | TR48X3.0LH      | <b>\$884</b>  |
| 92MM      | 21         | TR48X3.0-LH     | <b>\$850</b>  |
| x 99MM    | 22/30      | TR60X3.0-LH     | <b>\$1052</b> |
| 100MM     | 30         | TR52X3.0-LH     | <b>\$1052</b> |
| 110MM     | 30         | TR55X4.0-LH     | <b>\$1209</b> |
| 120MM     |            | TR62X10-LH      | <b>\$1282</b> |
| 130MM     | 30         | TR65X10-LH      | <b>Quote</b>  |
| 140MM     |            | TR70X9.5-LH     | <b>Quote</b>  |

x = Requires thread adapter.