

KAWAGUCHI Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
25MM	18	TR13X2.0-LH	\$316
25MM	38	TR13X2.0-LH	\$316
25MM	18	TR15X2.0-LH	\$316
27MM	40	M14X2.0-LH	\$316
28MM	18	.625-11 TPI-LH	\$316
28MM	18	TR15.2.0-LH	\$316
28MM	19	TR15X2.0-LH	\$316
28MM	35	M15X1.5-LH	\$316
28MM	40	M15X1.5-LH	\$316
30MM	40	TR15X2.0-LH	\$316
30MM	40	M16X1.5-LH	\$316
30MM	40	M16X1.5-LH	\$316
34MM	32	TR18X2.0-LH	\$316
34MM	32	TR18X2.0-LH	\$316
34MM	40	M18X2.0-LH	\$316
34MM	40	M20X2.0-LH	\$316
35MM	28	TR20X2.0-LH	\$316
36MM	40	TR20X2.0-LH	\$316
x 36MM	40	M20X2.0-LH	\$316
37MM	30	TR20X2.0-LH	\$316

x = Requires thread adapter.

KAWAGUCHI Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
38MM	35	M22X2.0-LH	\$351
40MM	27	TR20X2.0-LH	\$351
40MM	30	TR20X2.0 LH	\$351
40MM	35	TR20X2.0-LH	\$351
40MM	40	.750-10-LH	\$351
x 42MM	40	TR24X3.0-LH	\$351
45MM	40	TR25X3.0-LH	\$359
45MM	40	TR25X3.0-LH	\$359
45MM	40	1.000-08 TPI-LH	\$359
48MM	35	TR28X3.0-LH	\$372
50MM	40	TR28X3.0-LH	\$372
50(K1801)	40	TR28X3.0-LH	\$372
x 50MM	35	TR30X3.0-LH	\$372
50(KS175)	32	M26X2.0-LH	\$372
50MM	35	TR24X3.0-LH	\$372
50(KA200B)	40	TR26X3.0-LH	\$372
50MM	36	TR30X3-LH	\$372
50MM	40	TR26X3.0-LH	\$372
52MM	45	1.000-08 TPI-LH	\$426
55(KM220B)	40	TR30X3.0-LH	\$431

x = Requires thread adapter.

KAWAGUCHI Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
55MM	35	TR28X3.0-LH	\$431
58MM	40	TR34X4.0-LH	\$516
58MM	35	TR30X3.0-LH	\$516
x 58MM	25	TR34X4.0-LH	\$516
x 60MM	40	TR34X4.0-LH	\$518
60MM	40	TR34X4.0-LH	\$518
60MM	40	TR34X4.0-LH	\$518
60MM	40	TR34X4.0-LH	\$518
63MM	40	TR34X4.0-LH	\$526
63MM	40	TR34X4.0-LH	\$526
63MM	30	TR30X3.0-LH	\$526
65MM	35	TR34X4.0-LH	\$570
70MM	35	TR34X4.0-LH	\$606
x 70MM	35	TR40X4.0-LH	\$606
x 70MM	40	TR38X4.0-LH	\$606
x 72MM	40	TR40X4.0-LH	\$623
85MM	40	TR46X5.0-LH	\$782
90MM	40	TR46X5.0-LH	\$801
90MM	40	1.500-8 TPI-LH	\$801
x 100MM	40	TR52X5.0-LH	\$885

x = Requires thread adapter.