



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
18MM			\$316
25MM	60	M12X1.0-LH	\$316
25MM	90	M12X1.75-LH	\$316
30MM	60	M16X1.5-LH	\$316
34MM			\$316
35MM	90	M16X2.0-LH	\$316
35MM	60	M16X1.5-LH	\$316
40MM	60	M20X1.5-LH	\$333
42MM			\$351
50MM	60	M24X1.5-LH	\$412
50MM	90	M24X3.0-LH	\$412
60MM	90	M30X3.5-LH	\$516
70MM	90	M36X3.0-LH	\$586
x 80MM	90	M48X4.0-LH	\$804
x 90MM	90	M52X3.0-LH	\$891
100MM	90	M60X4.0-LH	\$1074
100MM	90	M60X4.0-LH	\$1074
x 100MM	90	M60X4.0-LH	\$1074
x 115MM	90	2.000-08 TPI-LH	\$1249
x 115MM	90	M68X4.0-LH	\$1249
130MM			Quote
150MM	90	M80X4.0-LH	Quote
170MM			Quote

x = Requires thread adapter.