



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

| RING DIA. | NOSE ANGLE | SCREW THREAD | 3T Style      |
|-----------|------------|--------------|---------------|
| 28MM      | 20         | M16X2.0-LH   | <b>\$316</b>  |
| 32MM      | 16         | M22X2.5-LH   | <b>\$316</b>  |
| 32MM      | 18         | M16X2.0-LH   | <b>\$316</b>  |
| 32MM      | 16         | M16X2.0-LH   | <b>\$316</b>  |
| 36MM      | 21.5       | M22X2.5-LH   | <b>\$316</b>  |
| 36MM      | 22         | M22X2.5-LH   | <b>\$316</b>  |
| 40MM      | 22         | M22X2.5-LH   | <b>\$436</b>  |
| x 45MM    | 26         | M27X3.0-LH   | <b>\$446</b>  |
| 45MM      | 30         | M22X2.5-LH   | <b>\$446</b>  |
| 50MM      | 26.3       | M27X3.0-LH   | <b>\$459</b>  |
| 50MM      | 27         | M27X3.0-LH   | <b>\$459</b>  |
| x 57MM    | 20         | M33X3.5-LH   | <b>\$479</b>  |
| x 62MM    | 26         | M36X4.0-LH   | <b>\$508</b>  |
| x 70MM    | 26         | M39X4.0-LH   | <b>\$656</b>  |
| 70MM      | 28         | M39X4.0-LH   | <b>\$656</b>  |
| 70MM      | 25         | M39X4.0-LH   | <b>\$656</b>  |
| x 80MM    | 30         | M45X4.5-LH   | <b>\$785</b>  |
| 80MM      | 25         | M45X4.5-LH   | <b>\$785</b>  |
| 90MM      | 30         | M48X5.0-LH   | <b>\$760</b>  |
| 105MM     | 30         | M56X5.5-LH   | <b>\$978</b>  |
| 105MM     | 30         | M56X5.5-LH   | <b>\$978</b>  |
| 120MM     | 30         | M60X5.5-LH   | <b>\$1297</b> |
| 120MM     | 30         | M60X5.5-LH   | <b>\$1297</b> |
| 135MM     | 30         | M64X6.0-LH   | <b>\$1374</b> |
| 150MM     | 30         | M76X6.0-LH   | <b>\$1835</b> |
| 150MM     | 60         | M80X4.0-LH   | <b>Quote</b>  |
| 175MM     | 30         | M85X6.0-LH   | <b>Quote</b>  |

x = Required thread adapter.