

# NATCO Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
1.875"	60	1.125-6 TPI-LH	<b>\$366</b>
1.875"	30	1.125-6 TPI-LH	<b>\$366</b>
2.25"	30	1.000-8 TPI-LH	<b>\$552</b>
2.25"	30	1.000-8 TPI-LH	<b>\$552</b>
3.25"	21	2.000-6 TPI-LH	<b>\$696</b>
3.25"	21	1.375-6 TPI-LH	<b>\$696</b>
5.75"		2.750-6 TPI-LH	<b>Quote</b>
70MM	15.5	1.125-6 TPI-LH	<b>\$575</b>
70MM	45	1.125-6 TPI-LH	<b>\$575</b>
90MM	21	1.500-6 TPI-LH	<b>\$760</b>
90MM	45	1.500-6 TPI-LH	<b>\$760</b>
105MM	20	1.750-6 TPI-LH	<b>\$1076</b>
120MM	21	2.000-6 TPI-LH	<b>\$1317</b>
135MM	23	2.250-6 TPI-LH	<b>\$1495</b>
135MM	23	3.500-6 TPI-LH	<b>\$1495</b>