



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
1.125"	60	.5625-18 TPI-LH	\$316
1.375"	60	.5625-18 TPI-LH	\$316
1.625"	60	.750-16 TPI-LH	\$373
1.75"	60	.750-16 TPI-LH	\$386
2"	60	1.000-8 TPI-LH	\$395
2.125"	60	1.000-8 TPI-LH	\$439
2.312"	60	1.000-8 TPI-LH	\$599
2.5"	60	1.250-8 TPI-LH	\$658
2.75"	60	1.375-8 TPI-LH	\$728
3.25"	60	1.500-8 TPI-LH	\$826
3.25"	60	1.500-8 TPI-LH	\$826
3.5"	60	1.750-8-TPI-LH	\$854
30MM	16	M18X2.5-LH	\$316
36MM	20	TR20x3.0-LH	\$316
x 42MM	22	TR27X3.0-LH	\$380
x 45MM	35	TR27X3.0-LH	\$386
48MM		TR27X3.0-LH	\$399
x 55MM	45	TR35X3.0-LH	\$450
58MM	11	TR35X3.0-LH	\$516
58MM	51	TR40X3.0-LH	\$516
x 65MM	51	TR40X3.0-LH	\$586
70MM	60	TR40X3.0-LH	\$586
x 70MM	16	TR40x3.0-LH	\$586
x 82MM	20	TR47X3.0-LH	\$688

x = Requires thread adapter.