

NEWBURY Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
1"	150	.500-13 TPI-LH	\$316
1"	45	.500-13 TPI-LH	\$316
1.125"	120	.625-11 TPI- LH	\$316
1.25"	150	.625-11 TPI-LH	\$316
1.25"	60	.625-11 TPI-LH	\$316
1.375"	60	.625-11 TPI-LH	\$316
1.375"	120	.625-11 TPI-LH	\$316
1.5"	42	.750-10 TPI-LH	\$316
1.5"	45	.750-10 TPI-LH	\$316
1.5"	150	.750-10 TPI-LH	\$316
1.5"	60	.750-10 TPI-LH	\$316
1.75"	60	.875-9 TPI-LH	\$338
1.75"	120	.875-9 TPI-LH	\$338
2"	60	1.000-8 TPI-LH	\$352
2"	150	1.000-8 TPI-LH	\$352
2.25"	60	1.000-8 TPI-LH	\$429
2.5"	60	1.000-8 TPI-LH	\$505
3"	60	1.750-5 TPI-LH	\$572
3"	60	1.750-5 TPI-LH	\$572