

PH HYDRAULICS Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
1"	90	.500-11 TPI-LH	\$316
1.25"	90	.625-11 TPI-LH	\$316
1.375"	90	.625-11 TPI-LH	\$316
1.5"	90	.625-11 TPI-LH	\$316
1.75"	90	.750-10 TPI- LH	\$580
2"	90	.875-9 TPI-LH	\$352
2.25"	90	.875-9 TPI-LH	\$426
2.5"	45	1.250-08 TPI-LH	\$508
2.5"	90	1.125-07 TPI- LH	\$508
3"	30	1.37506 TPI-LH	\$590
4'	60	2.0-06 TPI-LH	\$978
20MM	90	.375-16 TPI-LH	\$316
20MM	90	M10X.75-LH	\$316
25MM	90	.500-13 TPI-LH	\$316
28MM	90	.625-11 TPI-LH	\$316
32MM	90	M16X2.0-LH	\$316
35MM	90	.625-11 TPI-LH	\$316