

REED Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
1"			\$316
1.125"			\$316
1.375"		.625-11 TPI-LH	\$316
1.5"	45	.750-10 TPI-LH	\$316
1.625"-TE	120	.875-9 TPI-LH	\$316
1.625"	30	.750-10 TPI-LH	\$316
1.625"-TG	30	.875-9 TPI-LH	\$316
1.625"	60	.875-09 TPI-LH	\$316
1.75"-TD	45	.750-10 TPI-LH	\$337
2"-TE	120	1.000-8 TPI-LH	\$338
2"	60	1.000-8 TPI-LH	\$338
2"	45	1.000-8 TPI-LH	\$338
2.125"	60	1.000-8 TPI-LH	\$406
2.5"-TE	120	1.250-8 TPI-LH	\$507
2.5"-TG/TU	60	1.250-8 TPI-LH	\$507
2.5"-TD	45	1.250-8 TPI-LH	\$507
2.5"	20	1.250-8 TPI-LH	\$507
2.5"-TVS	45	1.125-12 TPI-LH	\$507
2.5"	120	1.125-12 TPI-LH	\$507
3"-TE	120	1.375-8 TPI-LH	\$590
3"-TG	60	1.375-8 TPI-LH	\$590

x = Requires thread adapter.

REED Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
3"-TD	45	1.375-8 TPI-LH	\$590
3"	20	1.375-8 TPI-LH	\$590
3"	30	1.375-8 TPI-LH	\$590
3.375"-TG	60	1.625-8 TPI-LH	\$743
3.375"-TD	45	1.625-8 TPI-LH	\$743
3.75"-TE	120	1.875-8 TPI-LH	\$824
3.75"-TG	60	1.875-8 TPI-LH	\$824
3.75"-TD	45	1.875-8 TPI-LH	\$824
3.75"	20	1.875-8 TPI-LH	\$824
4.125"	60	2.250-8 TPI-LH	\$997
4.125"	45	2.250-8 TPI-LH	\$997
4.25"	50	2.000-8 TPI-LH	\$997
4.5"-TG	60	2.500-8 TPI-LH	\$1090
4.5"-TD	45	2.500-8 TPI-LH	\$1090
x 4.75"	120	2.750-8 TPI-LH	\$1197
4.75"	60	2.125-8 TPI-LH	\$1197
5"	60	2.750-8 TPI-LH	Quote
31MM	30	.625-11 TPI-LH	\$316
80MM		1.625-6 TPI-LH	\$648
85MM	50	1.750-5 TPI-LH	\$743

x = Requires thread adapter.