

SANDRETTO Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
24MM-#8	40	M10X1.5-LH	\$316
28MM	45	M12X1.75-LH	\$316
30MM-#8	40	M12X1.75-LH	\$316
32MM	20	M14X2.0LH	\$316
35MM	30	M16X2.0-LH	\$316
35MM-#8	40	M14X2.0-LH	\$316
40MM	30	M18X2.5-LH	\$316
40MM#8(125T)	40	M16X2.0LH	\$316
40MM#8(85T)	30	M18X2.5-LH	\$316
45MM-#7	30	M20X2.5-LH	\$338
45MM-#8	40	M20X2.5-LH	\$338
50MM	30	M24X3.0-LH	\$352
50MM-#8	40	M24X3.0-LH	\$352
55MM-#7	30	M27X3.0-LH	\$414
55MM-#8	40	M27X3.0-LH	\$414
60MM	30	M30X3.5-LH	\$473
65MM	40	M30X3.5-LH	\$516
70MM-#7	38	M33X3.5-LH	\$580
75MM-#8	40	M33X3.5-LH	\$661
80MM-#8	40	M36X4.0-LH	\$716
80MM	30	M36X4.0-LH	\$716
80MM	26	M36X4.0-LH	\$716
90MM	30	M39X4.0-LH	\$780
90MM	40	M39X4.0-LH	\$780
90MM	30	M39X4.0-LH	\$780
105MM	30	M42X4.5-LH	\$978
105MM	40	M42X4.5-LH	\$978
120MM	33	M48X5.0-LH	\$1165
120MM	60	2.000-06 TPI-LH	\$1165
135MM	70	M56X5.5-LH	\$1462
135MM	36	M56X5.5-LH	\$1462