

STOKES Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
1"			\$316
1.25"	33	.5625-18 TPI-LH	\$316
1.25"	30	.625-11 TPI-LH	\$316
1.25"	90	.5625-18 TPI-LH	\$316
1.375"	90	.750-10 TPI-LH	\$316
1.375"	40	.625-18 TPI-LH	\$316
1.625"	90	.750-16 TPI-LH	\$316
1.75"	90	.750-10 TPI-LH	\$337
1.875"	90	.875-14 TPI-LH	\$337
2"	90	1.000-12 TPI-LH	\$352
2"	75	1.000-8 TPI-LH	\$352
2"	60	1.000-8-LH	\$352
2"	26	1.000-08 TPI-LH	\$352
2.5"	90	1.125-12 TPI-LH	\$505
2.5"	22	1.125-12 TPI-LH	\$505
2.75"	90	1.250-12 TPI-LH	\$559
2.75"	90	1.375-8 TPI-LH	\$559
3"	60	1.375-12 TPI-LH	\$607
3"	25	1.257 TPI-LH	\$607
3.5"	60	1.625-12 TPI-LH	\$637
3.612		2.000-8 TPI-LH	\$774
4"		1.750-12 TPI-LH	\$774