

TOSHIBA Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
18MM	50	M8X1.0-LH	\$316
24MM	90	M12X1.75-LH	\$316
25MM	30	M12X1.5-LH	\$316
25MM	60	M12X1.5-LH	\$316
25MM-ISE-30P	50	M12X1.5-LH	\$316
28MM-ISE	30	M15X1.5-LH	\$316
28MM-ISE	50	M15X1.5-LH	\$316
28MM-ISE	60	M15X1.5-LH	\$316
32MM-ISE-60T	50	M18X2.0-LH	\$316
32MM-ISE-60T	23	M18X2.0-LH	\$316
32MM	20	M18X2.0-LH	\$316
32mm	30	M18X2.0-LH	\$316
32MM	60	M18X2.0-LH	\$316
36MM-ISF	60	M22X2.0-LH	\$316
36MM	60	M22X2.0-LH	\$316
36MM-ISG	23	M22X2.0-LH	\$316
36MM	20	M22X2.0-LH	\$316
36MM	23	M22X2.0-LH	\$316
x 36MM	30	M22X2.0-LH	\$316
36MM	30	M22X2.0-LH	\$316
36MM	20	M22X2.0-LH	\$316
36MM	60	M22X2.0-LH	\$316
40MM-ISF	60	M22X2.0-LH	\$316
40MM-ISE	20	M22X2.0-LH	\$316
40MM	23	M22X2.0-LH	\$316
40MM-IS/ISC	30	M22X2.0-LH	\$316
40MM	60	M22X2.0-LH	\$316
40MM	\$60	M22X2.0-LH	\$316

TOSHIBA Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
45MM	30	M26X1.5-LH	\$338
45MM-ISF	60	M26X1.5-LH	\$338
45MM-ISG	60	M26X1.5-LH	\$338
45MM	60	M26X1.5-LH	\$338
50MM-ISE	20	M28X2.0-LH	\$352
50MM-ISI	30	M28X2.0-LH	\$352
50MM	23	M28X2.0-LH	\$352
50MM-ISE	60	M28X2.0-LH	\$352
50MM-ISF/G	60	M28X2.0-LH	\$352
50MM	30	M28X2.0-LH	\$352
50MM	30	M28X2.0-LH	\$352
55MM-ISI	30	M28X2.0-LH	\$399
55MM	23	M28X2.0-LH	\$399
55MM-ISF	60	M28X2.0-LH	\$399
55MM-ISG	60	M28X2.0-LH	\$399
55MM	60	M28X2.0-LH	\$399
60MM	20	M28X2.0-LH	\$473
60MM-ISF	60	M28X2.0-LH	\$473
60MM	30	M28X2.0-LH	\$473
60MM	23	M28X2.0-LH	\$473
60MM	60	M28X2.0-LH	\$473
70MM-ISF	60	M36X3.0-LH	\$586
70MM-ISG	60	M36X3.0-LH	\$586
70MM-ISE	23	M36X3.0-LH	\$586
70MM-ISGF	60	M36X3.0-LH	\$586
70MM-ISG	60	M36X3.0-LH	\$586
70MM-ISA	24	M32X2.0-LH	\$586
70MM	30	M32X2.0-LH	\$586

TOSHIBA Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
70MM	30	M36X3.0-LH	\$586
75MM	20	M40X2.0-LH	\$661
80MM-ISF/G	60	M42X3.0-LH	\$743
80MM	23	M42X3.0-LH	\$743
80MM-ISE	20	M42X3.0-LH	\$743
80MM-ISI	30	M36X3.0-LH	\$743
85MM	23	M42X3.0-LH	\$814
85MM	35	M42X3.0-LH	\$814
85MM	34	M42X3.0-LH	\$814
90MM	23	M45X4.0-LH	\$904
90MM-ISF/G	60	M45X4.0-LH	\$904
95MM	60	M45X4.0-LH	\$1019
100MM	60	M50X4.0-LH	\$1057
100MM	30	M50X4.0-LH	\$1057
100MM	20	M50X4.0-LH	\$1057
100MM	23	M50X4.0-LH	\$1057
105MM-ISF	60	M50X4.0-LH	\$1117
105MM-ISF	60	M50X4.0-LH	\$1117
115MM	20	M60X4.0-LH	\$1164
115MM	60	M60X4.0-LH	\$1164
115MM	23	M60X4.0-LH	\$1164
120MM	60	M60X4.0-LH	\$1282
125MM-ISE	23	M64X6.0-LH	\$1490
125MM	60	M64X6.0-LH	\$1490
125MM-ISF/G	60	M64X6.0-LH	\$1490
125MM	60	M64X6.0-LH	\$1490
140MM	23	M64X6.0-LH	\$1662
140MM	30	M64X6.0-LH	\$1662
140MM-ISF/G	60	M64X6.0-LH	\$1662
160MM	60	M85x4.0-LH	Quote