



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
20MM-35TON	30	M10X1.25-LH	\$316
20MM-35TON	30	M12X1.75-LH	\$316
24MM	30	M12X1.5-LH	\$316
24MM	30	M12X1.5-LH	\$316
24MM	45	M12X1.5-LH	\$316
28MM	30	M16X2.0-LH	\$316
28MM	45	M16X2.0-LH	\$316
32MM	30	M18X2.5-LH	\$316
32MM	45	M18X2.5-LH	\$316
36MM	30	M18X2.5-LH	\$316
36MM	45	M18X2.5-LH	\$316
40MM	30	M22X2.5-LH	\$360
40MM	45	M22X2.5-LH	\$360
46MM	30	M24X3.0-LH	\$390
46MM	45	M24X3.0-LH	\$390
46.1MM	30	M24X3.0-LH	\$390
48MM	30	M18X2.5-LH	\$419
50.05MM	30	M27X3.0-LH	\$419
50MM	45	M27X3.0-LH	\$419
55MM	30	M27X3.0-LH	\$451
55MM	45	M27X3.0-LH	\$451
60MM	30	M30X3.0-LH	\$494
68MM	30	M33X3.5-LH	\$518
75MM	30	M36X4.0-LH	\$584
83MM	30	M39X4.0-LH	\$693
83MM	30	M38x4.0-LH	\$693