

UBE Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
4.75	30	2.250-8 TPI0LH	\$1180
71MM	31	1.250-7 TPI LH	\$805
71MM	31	M39X4.0-LH	\$805
80MM	30	M45X4.5-LH	\$999
80MM	30	M45X4.5-LH	\$999
90MM	31	M48X5.0-LH	\$1042
100MM	31	M42X4.5-LH	\$1056
100MM	31	M56X5.5-LH	\$1056
112MM	32	2.000-8 TPI-LH	\$1078
112MM	30	M48X5.0-LH	\$1078
x 120MM	31	M68X6.0-LH	\$1159
120MM	30	M48X5.0-LH	\$1159
125MM	31	2.250X6-TPI-LH	\$1339
x 132MM	31	2.375-8 TPI-LH	\$1277
140MM	31	2.500-8 TPI-LH	\$1584
140MM	31	M80X6.0-LH	Quote
150MM		3.000-6.0-LH	Quote
160MM		M68X6.0-LH	Quote
190MM		M80X6.0-LH	Quote

x = Requires thread adapter.