

VANDORN Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
18MM	60	M10X1.5-LH	\$316
25MM	30	.500-13 TPI-LH	\$316
25MM	60	.500-13 TPI-LH	\$316
28MM	30	.500-13 TPI-LH	\$316
30MM	30	.625-11 TPI-LH	\$316
30MM	60	M12X1.75-LH	\$316
30MM	30	M16X2.0-LH	\$316
31MM	30	(55WHIT).625-14	\$316
35MM	45	.750-10 TPI-LH	\$316
35MM	60	M14X2.0-LH	\$316
35MM	30	.750-10 TPI-LH	\$316
38MM	30	.750-10 TPI-LH	\$316
40MM	30	.750-10 TPI-LH	\$316
40MM	60	M16X2.0-LH	\$316
50MM	30	1.000-8 TPI-LH	\$352
50MM	60	TR22.3.0-LH	\$352
50MM	20		\$352
50MM	22	TR22X3.0-LH	\$352
57MM	30	1.250-7 TPI-LH	\$445
57MM	20	1.250-7 TPI-LH	\$445

VANDORN Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
60MM	22	TR27X3.0-LH	\$466
60MM	30	1.000-10 TPI-LH	\$466
65MM	30	1.375-6 TPI-LH	\$518
65MM	20	1.375-6 TPI-LH	\$518
69MM	30	1.375-6 TPI-LH	\$611
70MM	60	TR30X3.0-LH	\$619
70MM	22	TR30X3.0-LH	\$619
70MM	30		\$619
75MM	30		\$661
75MM	20	1.375-6 TPI-LH	\$661
80MM	22	TR35X3.0-LH	\$694
80MM	30	TR35X3.0-LH	\$694
80MM	60	TR35X3.0-LH	\$694
80MM	30	M45X4.5-LH	\$694
80MM	30		\$694
80MM	20	1.375-6 TPI-LH	\$694
90MM	30	1.750-8 TPI-LH	\$780
90MM	20	1.750-8 TPI-LH	\$780
95MM	60	TR40X3.0-LH	\$826
95MM	22	TR40X3.0-LH	\$826

VANDORN Screwtips



The BMS 3T screwtip is manufactured in the United States from a high carbon/chrome steel for high wear resistance. It is a 3 piece design that is heat treated and precision ground for long life and positive shutoff. The threads are tempered to prevent breakage. The 3T screwtip is a repairable, low cost option that comes with a performance guarantee.

RING DIA.	NOSE ANGLE	SCREW THREAD	3T Style
105MM	30	1.750-8 TPI-LH	\$978
105MM	20	1.750-8 TPI-LH	\$978
110MM	60	TR50X3.0-LH	\$1096
110MM	22	TR50X3.0-LH	\$1096
110MM	30	M50X3.0-LH	\$1096
115MM	45	2.00008 TPI-LH	\$1197
115MM	20	2.000-8 TPI-LH	\$1197
120MM	30	2.000-8 TPI-LH	\$1282
120MM	30	M55X3.0-LH	\$1282
130MM	60	TR60X3.0-LH	\$1490
130MM	22	TR60X3.0-LH	\$1490
130MM	30	M60X3.0-LH	\$1490
135MM	40	2.50008 TPI-LH	\$1548
135MM	30	2.500-8 TPI-LH	\$1548
145MM	30	M70X3.0-LH	\$1671
155MM	40	3.250-04 TPI-LH	\$1752
155MM	30	M75X4.0-LH	Quote
165MM	30	M75X4.-LH	Quote
180MM	40	3.250-4 TPI-LH	Quote
185MM	30	M85X4.0-LH	Quote